












## CARATTERISTICHE TECNICHE - TECHNICAL FEATURES

	standards	characteristics or properties	declared values
	ISO 10545-3	assorbimento d'acqua water absorption	≤0.5%
	ISO 10545-4	resistenza alla flessione (R) breaking strength	35 N/mm <sup>2</sup>
	ISO 10545-13	resistenza agli acidi resistance to acid	GLA
	ISO 10545-7	resistenza all'abrasione (PEI) resistance against abrasion (PEI)	IV
	ISO 10545-12	resistenza al gelo frost resistance	resiste frost proof
	ISO 10545-14	resistenza alle macchie stain resistance	5
	ISO 10545-2	planarità surface flatness	±0.5%
		spessore thickness	10 mm
	DIN 51097 DIN 51130 DCOF BOT3000	coefficiente d'attrito (scivolosità) static coefficient of friction	A R9 >0.42
	GRIP DIN 51097 DIN 51130 DCOF BOT3000	coefficiente d'attrito (scivolosità) static coefficient of friction	A+B+C R12 >0.42
		variazioni cromatiche color shade	V2 variazione leggera V2 slight variation



Ceramics of Italy

unicom srl

via flumendosa 7 - 41042 fiorano modenese - modena - italy

T +39 (0)536 926011 - F italy +39 (0)536 926038 - F world +39 (0)536 926033 - F europe +39 (0)536 926023

printed and bound in Italy

© 2017 unicom srl - all rights reserved