

CHANGE THE WAY YOU WORK

WITH KIESEL BRAND THINSETS

- Engineered to save time and perform like nothing else in the market.
- From installing small mosaics to thin gauge porcelain slabs, we have you covered.
- All Kiesel thinsets are made in Germany with the highest-grade raw materials and the latest technologies.
- Kiesel thinsets are self-curing, S1 & S2 rated and set the industry standard for non-sag, exceeding the requirements.
- The abundant transfer from our wet mixtures allows you to achieve better coverage with less effort.
- Get more out of your thinset! The lightweight fillers and specialty raw materials used in our formula allow our 33lb bag to cover 30-50% more than a 50lb bag, making the price per square foot comparable to less expensive thinsets.
- If green is what you are looking for, look no further than Kiesel with our EMICODE EC1 Plus rated 0,0 g/L VOC and approximately 25% post-consumer recycled products with dust-reduced technology*.
- Our thinsets are freeze-thaw stable, suitable for interior/exterior and submerged applications*.

| | Ready to grout in (hours) | Mortar flexibility (mm) | Interior | Exterior | Submersible | Floor | Wall | Ceiling | Large format | Slab | Thin GA slab |
|-----------------------|---------------------------|-------------------------|----------|----------|-------------|-------|------|---------|--------------|------|--|
| ✓ Good for | | | | | | | | | | | |
| ♥ Excellent for | | | | | | | | | | | |
| Servolight | 12 | 2.5-5 | ✓ | ✓ | ✓ | ✓ | ♥ | ♥ | ♥ | ✓ | Interior Walls* |
| Servolight S2 | 12 | ≥5 | ♥ | ♥ | ♥ | ♥ | ♥ | ♥ | ♥ | ♥ | Interior Floors** Exterior Walls* Exterior Floors* |
| Servoflex Trio | 12 | 2.5-5 | ✓ | ✓ | ✓ | ♥ | | | ♥ | ♥ | |
| Servoflex 5 | 4-6 | 2.5-5 | ♥ | ♥ | ♥ | ♥ | ✓ | | ✓ | ✓ | Interior Walls* |



New premium thinset/medium bed mortar with accelerated curing



WWW.CA.KIESEL.COM
1-800-KIESEL1

** This flyer serves as general information and should only be used as such. For more relevant details, application processes, suitability and environmental info before commencing installation work, please visit our USA website at www.ca.kiesel.com



*Coverage is approximate and is given for estimating purposes only. It may vary according to substrate conditions and other factors. At 68 °F (+20 °C) and 65 % relative humidity. Higher temperatures and low humidity decrease, lower temperatures and high humidity increase this value respectively. Avoid air entrapment doing exterior and underwater installations. Apply mortar on the substrate and backside of tiles (back-buttering procedure). Lift tiles and check for proper mortar transfer. Always check the latest technical data sheet.



Servolight

Premium extended coverage flexible thin set mortar

- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy coverings and porcelain slabs (GTPP)
- excellent for wall and floor tile installations
- smooth and creamy consistency, contains 25% post consumer recycled content
- freeze / thaw stable, self curing, 0.0 g/L VOC
- interior, exterior and submergible applications

Coverage:

1/4" x 1/4" x 1/4" sq notched trowel approx. 103 sq ft per bag
 1/2" x 1/2" x 1/2" sq notched trowel approx. 50 sq ft per bag

A 118.4
C2 TE-S1



54 x 33 lbs
Item no. 80010



Servolight S2 SuperTec

Premium extremely flexible extended coverage thin set mortar

- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy coverings and porcelain slabs (GTPP)
- excellent for wall and floor tile installations
- smooth and creamy consistency, contains 25% post consumer recycled content
- freeze / thaw stable, self curing, 0.0 g/L VOC
- interior, exterior and submergible applications

Coverage:


3/16" x 1/4" x 1/4" sq notched trowel approx. 117 sq ft per bag
 1/2" x 1/2" x 1/2" sq notched trowel approx. per 58 sq ft per bag

A 118.4
C2 TE-S2



54 x 33 lbs
Item no. 80081

200 x 6.6 lbs
Item no. 13103



Servoflex-Trio-SuperTec

Premium flexible full transfer thin set and medium bed mortar

- thinset and medium bed mortar up to 3/4" thickness
- one component, no additives required
- up to twice the coverage of a standard thin-set mortar
- easy to trowel with extended open time, light grey
- non-sag formula for large-and-heavy floor tiles
- smooth and creamy consistency, contains 25% post consumer recycled content
- adjustable mortar consistency
- full mortar transfer, no billowing of mortar through joints
- can also be used over heated screeds, balconies and patios
- freeze / thaw stable, self curing, 0.0 g/L VOC
- interior, exterior and submergible applications
- water ratio adjustable mortar consistency

Coverage:

1/4" x 1/4" x 1/4" sq notched trowel approx. 134 sq ft per bag
 1/2" x 1/2" x 1/2" sq notched trowel approx. 65 sq ft per bag

A 118.4
C2 E-S1



54 x 44 lbs
White item no. : 80022
Grey item no. 80024



Servoflex 5 royal SuperTec

Premium thinset, medium bed and leveling/repair mortar with an accelerated curing

- thinset and medium bed mortar up to 3/4" thickness.
- for walls and floors installations.
- dust reduced, light grey color.
- for interior, exterior and submergible applications, excellent for uncoupling membranes.
- efflorescence free, aluminate cement based with acrylic polymers. S1: normal-deformability ≥ 0.1" (≥ 2.5 mm) and ≤ 0.2" (≤ 5 mm)
- fully cured after 12 hours for commercial traffic*.
- fully walkable and ready to grout after 4 hours over absorbent substrates and under and over uncoupling membranes after 6 hours*
- extended working time. Up to 2.5 hours bucket time with 20-30 minutes open time.*
- can be exposed to rain after 4-6 hours*
- post-consumer recycled content -25%, 0.0 g/L VOC
- extended coverage approximately 30%
- water ratio adjustable mortar consistency
- continued Mortar Consistency Technology. Clip-system friendly at 1.55 US gal water ratio.
- non-sag exceeding industry requirements
- excellent adhesion and accelerated drying/curing times over/under uncoupling membranes

Coverage:

1/4" x 1/4" x 1/4" sq notched trowel approx. 103 ft. per bag
 1/2" x 1/2" x 1/2" sq notched trowel approx. 50 ft. per bag

A 118.15 LHT
C2 FTE-S1



72 x 27.5 lbs
Item no. 13155

