

SIMBOLI E SPECIFICHE TECNICHE - SYMBOLS AND TECHNICAL SPECIFICATIONS - SYMBOLE UND TECHNISCHE SPEZIFIKATIONEN - SYMBOLES ET SPÉCIFICATIONS TECHNIQUES

**TONALITÀ MISCELATE
MIXED COLOURS - GEMISCHTE FARBEN - COULEURS MÉLANGÉES**



ASPETTO UNIFORME
UNIFORM APPEARANCE



LIEVE VARIAZIONE
LIGHT VARIATION



MODERATA VARIAZIONE
MODERATE VARIATION



FORTE STONALIZZAZIONE
SUBSTANTIAL VARIATION

**CARATTERISTICHE TECNICHE
TECHNICAL FEATURES - TECHNISCHE BEZEICHNUNGEN - CARACTÉRISTIQUES TECHNIQUES**



PAVIMENTO
FLOOR TILES



RIVESTIMENTO
WALL TILES



ABITAZIONE
HOUSE



PORTICATO
PORCH



HOTEL
HOTEL



RESISTENZA
ATTACCO CHIMICO
ETCHING RESISTANCE



IGIENICITÀ
HYGIENE



BASSO ASSORBIMENTO
LOW ABSORPTION



RESISTENZA
ALLE MACCHIE
STAIN RESISTANCE



RESISTENZA
AL GELO
FROST RESISTANCE



SPESSORE
THICKNESS



RESISTENZA SCIVOLOSITÀ
SLIP RESISTANCE

**SPECIFICITÀ DEL PRODOTTO
TECHNICAL SPECIFICATIONS OF THE PRODUCT - TECHNISCHE SPEZIFIKATIONEN DES PRODUKTES - SPÉCIFICATIONS TECHNIQUES DU PRODUIT**



RETTIFICATO
RECTIFIED



LAPPATO
POLISHED



COLORATO IN MASSA
FULL BODY COLOURED

**I GRADI DEI PEI
PEI RATING - PEI RATING - EVALUATION DES PEI**

Secondo la norma UNI EN ISO 10545/7,
il PEI determina la resistenza all'abrasione
della superficie delle piastrelle smaltate.
According to UNI EN ISO 10545/7, PEI
determines the wear resistance of the
surface of glazed tiles.



PIASTRELLE CONSIGLIATE
PER LOCALI A MEDIO/ALTO
TRAFFICO.
TILES RECOMMENDED FOR
AREAS WITH HEAVY TRAFFIC.



PIASTRELLE CONSIGLIATE
PER LOCALI AD ALTO
TRAFFICO.
TILES RECOMMENDED FOR AREAS
WITH HEAVY TRAFFIC.



PIASTRELLE CONSIGLIATE
PER LOCALI A TRAFFICO
PESANTE.
TILES RECOMMENDED FOR
AREAS WITH HEAVY TRAFFIC.

CONSIGLI PER LA POSA - SUGGESTIONS FOR LAYING - RATSCHLÄGE FÜR DIE VERLEGUNG - CONSEILS POUR LA POSE

Viste le caratteristiche delle serie si consiglia:	Considering the characteristics of this series we suggest:	Im Hinblick auf die Eigenschaften der Serie man empfiehlt:	Vues les caractéristiques de la serie nous conseillons:
- Rivestimento Fuga di 2-3mm.	- Wall tiles 2-3 mm. joint	- Wandfliesen 2-3 mm. Fuge	- Carreaux pour murs Joint 2/3mm.
- Pavimento Si consiglia la posa affiancata o a correre sfalsata 4/5 - con fuga di 3-4mm.	- Floor tiles ined up laying or 4/5 staggered laying is suggested - 4/5mm joint	- Bodenfliesen Neben verlegt oder 4/5 versetzt 4/5 mm Fuge	- Carreaux pour sol Il est conseillé une pose alignée - Joint 4-5 mm

SIMBOLI LETTURA LISTINO - SYMBOLS PRICE LIST INDICATION - SYMBOLE DER PREISLISTE - SYMBOLES DE LA LISTE DE PRIX

**SIMBOLI LETTURA LISTINO
SYMBOLS PRICE LIST INDICATION - SYMBOLE DER PREISLISTE - SYMBOLES DE LA LISTE DE PRIX**



NATURALE euro/mq
NATURAL euro/mq



RETTIFICATO euro/mq
RECTIFY euro/mq



LAPPATO euro/mq
POLISHED euro/mq



PEZZO euro/pz.
PICES euro/pz.



PEZZO LAPPATO euro/pz.
PICES POLISHED euro/pz.

LISTINO PREZZI

CODICE CODE Nr.	PREZZO PRICE EURO	CODICE CODE Nr.	PREZZO PRICE EURO	CODICE CODE Nr.	PREZZO PRICE EURO
1	5,5	11	37	21	54
2	7	12	40	22	55
3	12	13	41	23	57
4	14	14	42	24	59
5	16	15	44	25	60
6	18	16	45	26	65
7	25	17	47	27	70
8	27	18	51	28	75
9	30	19	52	29	80
10	34	20	53	30	85

IMBALLI E PESI - PACKING AND WEIGHTS - VERPACKUNGEN UND GEWICHTE - EMBALLAGE ET POIDS

Formato Size Format Format	SCATOLA/BOX			Kg./mq. Sqm/mq Kg/mq kg/mq	PALLET			FORNITO
	Pz./Scat. Pcs/Box Pcs/Boite	mq./Scat. Sqm/Box Qm/Kart. Mc/Boite	Kg./Scat. Kg/Box Kg/Kart. Kg/Boite		Scatole Boxes Kartons Boites	mq Sqm Qm Mc	Kg. Kg Kg Kg	
60x120	2	1,44	30,4	22,22	35	50,40	1064	-