

Product Item Numbers



6.4 Schluter®-DITRA-HEAT		Uncoupling and waterproofing membrane
Item No.	Item	Dimensions
DH5 12M	Roll	3' 2-5/8" x 41' 10-3/4" = 134.5 ft ² (0.98 m x 12.76 m = 12.5 m ²)
DH5 MA	Sheet	3' 2-5/8" x 2' 7-3/8" = 8.4 ft ² (0.98 m x 0.80 m = 0.78 m ²)

U.S. Pat. No. 8,950,141, and U.S. DES. PAT. No. D706459
Canada © Schluter Systems L.P. and other patents pending.



6.4 Schluter®-DITRA-HEAT-DUO		Uncoupling and waterproofing membrane with thermal break
Item No.	Item	Dimensions
DHD8 10M	Roll	3' 2-5/8" x 33' 6-1/2" = 108 ft ² (0.98 m x 10.20 m = 10 m ²)
DHD8 MA	Sheet	3' 2-5/8" x 2' 7-3/8" = 8.4 ft ² (0.98 m x 0.80 m = 0.78 m ²)

Patent pending



6.4 Schluter®-DITRA-HEAT-PS		Peel & stick uncoupling and waterproofing membrane
Item No.	Item	Dimensions
DHPS5 12M	Roll	3' 2-5/8" x 41' 10-3/4" = 134.5 ft ² (0.98 m x 12.76 m = 12.5 m ²)
DHPS5 MA	Sheet	3' 2-5/8" x 2' 7-3/8" = 8.4 ft ² (0.98 m x 0.80 m = 0.78 m ²)



6.4 Schluter®-DITRA-HEAT-DUO-PS		Peel & stick uncoupling and waterproofing membrane with thermal break
Item No.	Item	Dimensions
DHDPS8 10M	Roll	3' 2-5/8" x 33' 6-1/2" = 108 ft ² (0.98 m x 10.20 m = 10 m ²)
DHDPS8 MA	Sheet	3' 2-5/8" x 2' 7-3/8" = 8.4 ft ² (0.98 m x 0.80 m = 0.78 m ²)



6.4 Schluter®-DITRA-HEAT-E-HK

Heating Cable

Item No.	Heating Cable Length		Area Covered per Cable Spacing				Total Power (W)	Avg. Power per Unit Area per Cable Spacing				Current (Amps)
			Regular 3 Stud		Alternating 3-2 Stud			Regular 3 Stud		Alternating 3-2 Stud		
	(ft)	(m)	(ft²)	(m²)	(ft²)	(m²)		(Watts/ft²)	(Watts/m²)	(Watts/ft²)	(Watts/m²)	
Heating Cable (120 V)												
DHE HK 120 11	35.3	10.8	10.7	1.0	8.9	0.8	135	12.6	136	15.2	164	1.1
DHE HK 120 16	52.9	16.1	16.0	1.5	13.3	1.2	203	12.7	136	15.2	164	1.7
DHE HK 120 21	70.5	21.5	21.3	2.0	17.8	1.7	270	12.7	136	15.2	164	2.3
DHE HK 120 27	88.2	26.9	26.7	2.5	22.2	2.1	338	12.7	136	15.2	164	2.8
DHE HK 120 32	105.8	32.2	32.0	3.0	26.7	2.5	405	12.7	136	15.2	164	3.4
DHE HK 120 38	124.1	37.8	37.5	3.5	31.3	2.9	475	12.7	136	15.2	164	4.0
DHE HK 120 43	141.1	43.0	42.7	4.0	35.6	3.3	540	12.7	136	15.2	164	4.5
DHE HK 120 51	169.8	51.8	51.4	4.8	42.8	4.0	650	12.7	136	15.2	164	5.4
DHE HK 120 64	212.9	64.9	64.4	6.0	53.7	5.0	815	12.7	136	15.2	164	6.8
DHE HK 120 73	240.2	73.2	72.7	6.8	60.6	5.6	920	12.7	136	15.2	164	7.7
DHE HK 120 83	275.5	84.0	83.3	7.7	69.4	6.5	1055	12.7	136	15.2	164	8.8
DHE HK 120 92	303.0	92.4	91.7	8.5	76.4	7.1	1160	12.7	136	15.2	164	9.7
DHE HK 120 102	336.9	102.7	101.9	9.5	84.9	7.9	1290	12.7	136	15.2	164	10.7
DHE HK 120 113	372.2	113.4	112.6	10.5	93.8	8.7	1425	12.7	136	15.2	164	11.9
DHE HK 120 134	444.0	135.3	134.3	12.5	111.9	10.4	1700	12.7	136	15.2	164	14.2
Heating Cable (240 V)												
DHE HK 240 11	35.3	10.8	10.7	1.0	8.9	0.8	135	12.6	136	15.2	164	0.6
DHE HK 240 16	53.1	16.2	16.1	1.5	13.4	1.2	203	12.6	136	15.2	164	0.8
DHE HK 240 21	70.6	21.5	21.4	2.0	17.8	1.7	270	12.7	136	15.2	164	1.1
DHE HK 240 27	88.2	26.9	26.7	2.5	22.2	2.1	338	12.7	136	15.2	164	1.4
DHE HK 240 32	105.8	32.2	32.0	3.0	26.7	2.5	405	12.7	136	15.2	164	1.7
DHE HK 240 38	124.1	37.8	37.5	3.5	31.3	2.9	475	12.7	136	15.2	164	2.0
DHE HK 240 43	141.0	43.0	42.6	4.0	35.5	3.3	540	12.7	136	15.2	164	2.3
DHE HK 240 53	176.3	53.7	53.3	5.0	44.4	4.1	675	12.7	136	15.2	164	2.8
DHE HK 240 64	211.6	64.5	64.0	5.9	53.3	5.0	810	12.7	136	15.2	164	3.4
DHE HK 240 75	248.2	75.7	75.1	7.0	62.6	5.8	950	12.7	136	15.2	164	4.0
DHE HK 240 85	282.1	86.0	85.3	7.9	71.1	6.6	1080	12.7	136	15.2	164	4.5
DHE HK 240 103	339.4	103.4	102.7	9.5	85.6	7.9	1300	12.7	136	15.2	164	5.4
DHE HK 240 129	425.8	129.8	128.8	12.0	107.3	10.0	1630	12.7	136	15.2	164	6.8
DHE HK 240 145	480.5	146.5	145.3	13.5	121.1	11.3	1840	12.7	136	15.2	164	7.7
DHE HK 240 167	551.0	167.9	166.7	15.5	138.9	12.9	2110	12.7	136	15.2	164	8.8
DHE HK 240 183	605.9	184.7	183.3	17.0	152.7	14.2	2320	12.7	136	15.2	164	9.7
DHE HK 240 204	673.8	205.4	203.8	18.9	169.9	15.8	2580	12.7	136	15.2	164	10.7
DHE HK 240 225	744.4	226.9	225.2	20.9	187.7	17.4	2850	12.7	136	15.2	164	11.9



6.4 Schluter®-DITRA-HEAT-E-RS1/WiFi-/RT-/R Digital thermostats with remote floor temperature sensors

Item No.	Description
DHE RT 105/BW	SMART WiFi app-based programmable thermostat in white, compatible with major voice controlled automation software
DHE RT 104/BW	WiFi and touchscreen programmable thermostat in white
DHE RT 102/BW	Touchscreen programmable thermostat in white
DHE RT 103/BW	Non-programmable thermostat in white



6.4 Schluter®-DITRA-HEAT-E-RRS/-RR

Power module

Item No.	Description
DHE RR 2/BW	Power module for use with the DHE RT 105/BW
DHE RR 1/BW	Power module for use with DHE RT thermostats